

WHAT IS CLAIMED IS:

1                   1.       A method for executing foreign code on a host system, said host  
2 system having a storage means for storing foreign code and a database of translated binary  
3 code, said method comprising the steps of:

4                   identifying a sequence of foreign code;  
5                   determining if said sequence of foreign code has corresponding translated  
6 binary code stored in said database;

7                   if said determining step identifies corresponding translated binary code,  
8 transferring said corresponding translated binary code from said database to memory  
9 associated with said computer system;

10                  if said determining step does not identify corresponding translated binary  
11 code, translating said foreign code to obtain a corresponding sequence of translated binary  
12 code in said memory.

13                  2.       The method of claim 1 further comprising the step of saving said  
14 sequence of corresponding translated binary code to said database.

15                  3.       The method of claim 2 further comprising the step of saving a hash  
16 value associated with said sequence of corresponding translated binary code.

17                  4.       The method of claim 3 further comprising the step of saving a portion  
18 of said foreign code.

19                  5.       The method of claim 3 further comprising the step of saving loader  
20 information.

21                  6.       The method of claim 2 further comprising the step of saving an  
22 identifying value associated with said sequence of corresponding translated binary code.

23                  7.       The method of claim 6 wherein said saving step comprises the step of  
24 saving a disk sector value.

25                  8.       The method of claim 1 wherein said identifying as step further  
26 comprises the steps of:

27                   transferring a sequence of foreign code from a disk drive sector;  
28                   using the value of said disk drive sector as an index to said database; and

5 determining if said database contains translated binary code at a location  
6 identified by said index.

1 9. The method of claim 1 wherein said identifying as step further  
2 comprises the steps of:  
3 determining if said sequence of foreign code has corresponding translated  
4 binary code stored in said database.

1 10. A method for executing foreign code on a host system, said host  
2 system having a memory and at least one disk drive for storing foreign code and a database of  
3 binary code, said method comprising the steps of:

4 identifying the location where the sequence of foreign code is stored on said  
5 disk drive;

6 using said location as an index to said database;  
7 if said location correspond to binary code stored in said database, transferring  
8 said corresponding translated binary code from said database to said memory;  
9 if said location does not correspond to binary code stored in said database,  
10 translating said foreign code to obtain a sequence of translated binary code in said memory.

11. The method of claim 10 further comprising the step of saving said  
sequence of translated binary code to said database at a location defined by said index.

12. The method of claim 10 wherein said translating step further comprises  
the steps of:

3 decoding said foreign code to obtain a sequence of semantic substitutions for  
4 said foreign code;  
5 optimizing said sequence of semantic substitutions; and  
6 monitoring the translation process to support coherence with the foreign code.

1 13. The method of claim 12 further comprising the step of saving said  
2 sequence of translated binary code to said database at a location defined by said index.

1 14. The method of claim 12 further comprising the step of saving said  
2 sequence of translated binary code to said database at a location defined by said location  
3 where said database is stored on second disk drive.

1           15.     In a computer system having a first architecture and adapted to execute  
2 a host code, said computer system adapted for executing a foreign code different from said  
3 host code, said computer system comprising:

4           a central processor having a plurality of execution units each adapted to  
5 execute a plurality of operations in parallel;

6           a memory unit having a first virtual memory space for storing foreign code  
7 and a second virtual memory space for storing host code, said host code corresponding to said  
8 foreign code;

9           a dynamic binary translation processor for interpreting said foreign code at  
10 run-time;

11           means for optimizing said host code to improve execution speed of said host  
12 code;

13           a dynamic analysis processor for monitoring the execution of translated binary  
14 code and providing memory management functions relating to maintaining host code  
15 compaction in said second virtual memory space.

16           a code database for storing at least a portion of said host code corresponding to  
17 said foreign code.

18           16.     The system of claim 15 further comprising means for determining  
19 whether a selected portion of said foreign code corresponds to a portion of said host code  
20 stored in said database.

21           17.     The system of claim 16 wherein said determining means further  
22 comprises means for selectively invoking said translation processor, said optimizing means  
23 and said dynamic analysis processor to translate said selected portion of foreign code.

24           18.     The system of claim 16 wherein said determining means further  
25 comprises means for generating an index to specify a location in said database, said index  
26 derived from said foreign code.

27           19.     The system of claim 18 wherein said invoking means further comprises  
28 a hashing function to generate said index.

29           20.     The system of claim 18 wherein said invoking means further comprises  
30 means for recovering a storage location of said foreign code to generate said index.

1                   21.     The system of claim 20 further comprising a disk drive for storing said  
2 foreign code in at least one sector of said disk drive.

1                   22.     The system of claim 16 further comprising a disk drive for storing said  
2 foreign code in at least one sector of said disk drive.

1                   23.     The system of claim 16 further comprising a disk drive for storing said  
2 foreign code in at least one sector of said disk drive and a second disk drive for storing said  
3 database.

093353360  
"44"  
0330